



HDTVI AHD CVBS SMP

KEY FEATURES

- 4 in 1 dome PRO series with Smart IR of 60 m for outdoors
- 1/2,7" CMOS, 5MP
- 4 in 1 output (HDCVI / HDTVI / AHD / 960H) switch by OSD or DAHUA-498 controller
- 2,7 ~12 mm motorized lens (98° ~ 34°)
- 0,02 lux
- ICR filter
- OSD, AWB, AGC, BLC, HLC, digital WDR, 2D-NR
- Built in microphone
- IP67
- 3AXIS

FEATURES

- 1/2,7" CMOS sensor, 5 MP
- Digital resolution: 5MP (2592x1944)
- Frames per second: 20 fps @5MP, 25 fps @4MP/1080P
- 4 in 1 output switch by OSD or via DAHUA-498 UTC controller
- 0,02 lux F1.8 (color, 30IRE) / 0 lux (IR on)
- Removable mechanical filter
- Smart IR: 2 led, 60 meters
- 2,7 ~ 12 mm motorized lens
- 98° ~ 34°(H) viewing angle
- Motorized focus control
- OSD via coaxial (700m range)
- Auto/manual white balance
- Automatic gain control
- BLC, HLC
- Digital WDR
- 2D noise reduction
- Built in microphone
- Power supply: 12V DC (±30%)
- Consumption: 8,2W (max.)
- Working temperature: -40°C ~ +60°C
- RH: <95%
- IP67
- Aluminum case
- Dimensions: Ø122 x 104 mm
- Weight: 570 g
- 3AXIS: 0°~360°(PAN), 0°~78°(TILT), 0°~360°(Rotation)