

16 CH IP NVR IP . H265/H264/MPEG4



## KEY FEATURES

- 16 CH IP NVR IP
- H.265/H.264/MPEG4
- 16 CH @ 1080P
- Display up to 12MP
- Recording: 12MP, 8MP, 6MP, 5MP, 4MP, 3MP, 1080P, UXGA, 720P, 4CIF, etc
- Recording 160 Mbps
- VGA @ 1080P and HDMI @ 4K
- 2 way audio
- Alarm: 4 in / 1 out
- 2 HDD SATA

## FEATURES 16 CH IP NVR, H.265/H.264/MPEG4- DUAL O/S SYSTEM

- Enabled POS funcion up to 4 POS
- 1 LPR channel supported (done by LPR camera function)- VCA events supported generated by cameras (motion detection, tripwire, intrusion, etc.)- 16 IP camera input- Input bandwidth: 160 Mbps- Output bandwidth: 256 Mbps- VGA (1080P) and HDMI (4K, 2K) video output- 2 way audio: 1 RCA in / 1 RCA out- Display resolution: 12MP, 8MP, 6MP, 5MP, 4MP, 3MP, 1080P, UXGA, 720P, VGA, 4CIF, DCIF, 2CIF, CIF, QCIF- Recording resolution: 12MP, 8MP, 6MP, 5MP, 3MP, 1080P, UXGA, 720P, VGA, 4CIF, DCIF, 2CIF, CIF, QCIF- Live display up to: 12MP- 16 channel synchronized playback- Decoding capacity: 16 CH @ 1080P, 4 CH @ 4K/8MP- Alarm channels: 4 in / 1 out- Storage: 2x SATA up to 6TB (HDD not included)- Network interface: Ethernet RJ45 (10/100/1000M) auto-adaptive- Compatible with ONVIF- ANR technology- Intelligent search (for IP NEXTGEN cameras)- VCA supported of IP cameras- P2P cloud, DDNS DEMES, Push and channel zero- Plug&Play with IP NEXTGEN cameras- Connections: 1x USB 2.0, 1x USB 3.0- 16 independent ports on rear pannel (100Mbps) PoE+ 802.3af/at- Power supply: 100V ~ 240V AC- PoE consumption: ≤200W- NVR consumption: ≤15W (without HHD and PoE)- Working temperature: -10°C ~ +55°C- RH: 10~90% - Dimensions: 380 x 290 x 45 mm - Weight: ≤3 kg