

MC 270-S78

High Security Contact




Technical data

Installation method	Surface mount
Contact function	Normally Closed (NC)
Approvals	EN 50131-2-6 Grade 3, Class IIIA, VdS G 116032 Class C, SBSC 9-205, Class 3, F&P, NBÚ CZ Typ 3, NBÚ SK Typ 3
Contact rating	48 VDC / 500 mA / 10 VA
Magnet type	Alnico 5
Mounting on steel	Possible without accessories
Make distance (wood) mm	34
Sabotage distance (wood) mm	20
Make distance (steel) mm	25
Sabotage distance (steel) mm	17
Tamper protection	Yes
Connection	Cable
Housing material	Aluminium
Operating temperature range	-40°C - +70°C
Housing protection class	IP 67
Contact dimensions (L x W x H) mm	74 x 30 x 30
Magnet dimensions (L x W x H) mm	74 x 30 x 30
Grade	3



The MC 270-S78 set is intended for exposed environments where a more durable high security contact is needed, such as steel and iron and industrial gates, etc. The set consists of MC 270-C contact with NC contact function installed in MC 200-7 Al housing and an extra strong magnet in MC 200-8 Al housing, which allows for a wide opening gap. MC 270-S78 set contains a 1 m long stainless steel Flexi-tube protection (MC T4). Contact and magnet are paired. To ensure proper functionality, do not replace the contact or magnet alone.



ORDERING INFORMATION

Model	Description
MC 270-S78	High security contact set, NC, 6 m cable