

IP HYUNDAI NEXT GEN VANDAL DOME PERFORMANCE LINE WITH IR OF 30M, FOR OUTDOORS



KEY FEATURES

- IP HYUNDAI NEXT GEN vandal dome Performance Line with IR of 30m, for outdoors
- 2 MP
- H.265 + / H.265 / H.264 + / H.264 / MJPEG format
- 1/2.8" CMOS, 2MP
- Digital resolution 1080P @ 25FPS
- Mechanical filter
- 0.028 lux
- 2.8 ~ 12 mm motor lens (99.6 ° ~ 35 °)
- OSD, AGC, BLC, WDR 120dB , 3D-DNR, motion detection, privacy masks, fixed ROI zone Intelligent analysis IP67, IK10, 3AXIS, 12V DC, PoE

PerformanceLine **IP67** **P2P**

ONVIF **EMP**



FEATURES

- 1/2.8" CMOS sensor, 2 MP
- Up to 1080P (1920x1080) at 25 fps
- 2.8 ~ 12mm motor lens with autofocus
- H.265 +, H.265, H.264 +, H.264 video compression
- Dual stream
- WDR 120dB, BLC, 3DDNR, 1 ROI
- Analysis of up to 2 behaviors
- Infrared lighting up to 30 meters
- MicroSD card slot up to 128GB (card not included)
- IP67
- IK10
- Supports PoE

SPECS

- 1/2.8" CMOS sensor, 2 MP
- Digital resolution: 1080P (1920x1080), 1.3MP (1280x960), 720P (1280x720), etc.
- Compression format H.265+ / H.265 / H.264+ / H.264 / MJPEG
- Main Stream: 1080P, 1.3MP, 720P (25 fps)
- Secondary stream: 640x480, 640x360, 320x240 (25 fps)
- Day / night mode with removable mechanical filter
- IR: 30 meters
- 0.028 lux F2.0 color / 0.0028 lux F2.0 (B/W) / 0 lux IR On
- 2.8 ~ 12mm motor lens with autofocus
- Viewing angle: 99.6 ° ~ 35 ° (H), 53.5 ° ~ 20 ° (V), 118.6 ° ~ 40.2 ° (D)
- OSD menu
- Automatic gain control
- Backlight Compensation: BLC
- WDR 120dB
- 3D digital noise reduction
- 1 fixed ROI zone main stream
- Motion detection and privacy mask
- Adjust brightness, saturation, contrast, sharpness, image rotation adjustable using client software or web browser
- Intelligent analysis: Line crossing detection, intrusion detection
- MicroSD card slot up to 128GB (card not included)
- Reset button
- Network interface: RJ45 (10 / 100M) autoadaptive
- Network protocols: TCP / IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP™, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Bonjour
- Compatible with ONVIF (Profile S, G), ISAPI
- Plug & Play connection with NVR NEXTGEN
- DDNS DEMES compatible
- Compatible with IE8 +, Chrome 3144, Firefox30-51, Safari 8+ browsers

- Power supply: 12V DC (± 25%)
- Consumption: 10W (PoE 12W)
- Supports 802.3af PoE, class 3
- Working temperature: 30 ° C ~ + 60 ° C
- Humidity: 95% (without condensation)
- IP67
- IK10
- Metal case
- Dimensions: Ø153.3 x 111.6 mm
- Weight: 880 g
- 3AXIS: 0 ° ~ 355 ° (PAN), 0 ° ~ 75 ° (TILT), 0 ° ~ 355 ° (ROTATION)
- Power supply is not included