



KEY FEATURES

- IP dome with IR illumination of 30m, for outdoors, 2 MP
- H.265+, H.265, H.264+, H.264
- 1/2,8" CMOS, 2MP
- 1080P, 1,3MP, 720P, etc
- Mechanical filter
- 0,01 lux
- 2,8 mm fixed lens (95°)
- OSD, AGC, BLC, digital WDR , 3D-DNR, motion detection, privacy mask, ROI
- IP67, IK10
- 3AXIS

HYU-416N HYU-416N

IP DOME WITH IR ILLUMINATION OF 30M, FOR OUTDOORS, 2 MP

FEATURES

- 1/2,8" CMOS, 2 MP
- Digital resolution: 1080P (1920x1080), 1,3MP (1280x960), 720P (1280x720), etc.
- H.265+, H.265, H.264+, H.264
- Stream 1: 1080P, 1,3MP, 720P (25 fps)
- Stream 2: 704x576 (25 fps), 704x480 (30 fps), 640x480 (25/30 fps), 352x288 (25 fps), 352x240 (30 fps), 320x240 (25/30 fps)
- Day/night mode with removable mechanical filter
- IR illumination: 30 meters
- Minimum illumination: 0,01 lux F1.2 color / 0 lux IR On
- 2,8 mm fixed lens (95°)
- OSD menu, AGC, BLC, digital WDR, 3DDNR
- 1 fixed ROI
- Motion detection and privacy mask
- Bright adjustment, saturation, contrast, sharpness, mirror
- Network interface: RJ45 (10/100 BaseT)
- Network protocol: TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, NTP, UPnP, SMTP, IGMP, 802.1X, QoS, IPv6, Bonjour
- Compatible with ONVIF (Profile S, G), PSIA, CGI, ISAPI
- Plug&Play with NVR NEXTGEN
- Compatible with DDNS DEMES
- Power supply: 12V CC /4W (Max 6W PoE)
- PoE 802.3af supported
- Working temperature 30°C ~ +60°C
- RH: 95%
- IP67
- IK10
- Metal case
- Dimensions: Ø127 x 101 mm
- Weight: 350 g
- 3AXIS: wall and ceiling installation
- Power supply is not included