

AISENSE IP DOME OF 4MP WITH IR OF 30M, FOR OUTDOORS



## KEY FEATURES

- AIsense IP dome of 4MP with IR of 30m, for outdoors
- H.265+/H.265/H.264+/H.264/MJPEG
- 1/2,7" CMOS, 4MP
- 4MP@25 fps
- ICR
- 0,01 lux
- 2,8~12 mm (101°~29°) motor lens with autofocus
- OSD, AGC, BLC, WDR true 120dB, 3D-DNR, 1 fixed ROI
- IVS
- 2 way audio
- Alarm: 1 in / 1 out
- Reset button
- MicroSD
- Onvif, ISAPI
- IP67, IK10
- 3AXIS
- 12V DC
- PoE



### Aisense series

- Aisense is able to differentiate, with great precision, a human body and a vehicle on a stage with a large number of objects. Not only can it detect human and vehicle intrusion, it can also filter out false alarms that could have been triggered by moving objects that do not pose a threat.

### FEATURES

- 4MP at 25 fps
- 2,8~12 mm motor lens
- H.265+, H.265, H.264+, H.264
- WDR 120dB, BLC, 3DDNR, ROI
- False alarm filter by objective classification (Aisense)
- IR illumination up to 30 meters
- MicroSD up to 128GB (card is not included)
- IP67
- IK10
- PoE supported

### SPECS

- 1/2,7" CMOS sensor, 4 MP
- Digital resolution: 4MP (2688x1520), 1080P (1920x1080), 720P (1280x720), etc.
- H.265+/H.265/H.264+/H.264/MJPEG
- Stream 1: 4MP, 1080P, 720P (25 fps)
- Stream 2: 640x480, 640x360, 320x240 (25 fps)
- Day/night mode with removable mechanical filter
- IR illumination: 30 meter
- Minimum illumination: 0,01 lux F1.4 color (AGC On)
- 2,8 ~ 12 mm motor lens
- Viewing angle: 101°~29°(H), 54°~16°(V), 121°~34°(D)
- Automatic focus mode
- OSD menu
- White balance
- AGC
- BLC
- WDR true 120dB
- 3D digital noise reduction
- 1 fixed ROI stream 1 and stream 2
- Adjustment of brightness, saturation, contrast, sharpness, gain control and white balance through client software and web browser
- Smart functions: Detection of line crossing, intrusion detection, detection of entry or exit to region, false alarm filter by objective classification
- Audio: 1 in / 1 out
- Ambient noise filter
- Alarm: 1 in / 1 out

- Reset button
- MicroSD/SDHC/SDXC up to 128GB (card is not included)
- Network interface: RJ45 (10/100 BaseT)
- Network protocols: TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, UDP, Bonjour
- Compatible with ONVIF (Profile S, G), ISAPI
- Plug&Play with NVR NEXTGEN
- Compatible with DDNS DEMES
- Power supply: 12V DC
- Consumption: 0,9A, máx. 11W
- PoE 802.3af, Class 3
- Working temperature 30°C ~ +60°C
- RH: 95% (without condensation)
- IP67
- IK10
- Metal and plastic case
- Dimensions: Ø153,3 x 111,6 (L) mm
- Weight: 890 g
- 3AXIS: 0°~355°(PAN), 0°~75°(TILT), 0°~355°(Rotation)
- Power supply is not included