



PerformanceLine ~~IP67~~ **P2P**

ONVIF 4MP

HYU-773 HYU-773

IP HYUNDAI NEXT GEN DOME PERFORMANCE LINE WITH IR OF 30M, FOR OUTDOOR

KEY FEATURES

- IP HYUNDAI NEXT GEN dome Performance Line with IR of 30m, for outdoor
- 4 MP
- H.265 + / H.265 / H.264 + / H.264 / MJPEG format
- 1/3 " CMOS, 4MP
- Digital resolution of 4MP @ 20FPS
- Mechanical filter
- 0.02 lux
- 2.8 ~ 12 mm motor lens (92.8 ° ~ 29 °)
- OSD, AGC, BLC, WDR 120dB , 3D-DNR, motion detection, privacy masks, fixed ROI zone, IP67, IK10 3AXIS, 12V DC, PoE



FEATURES

- 1/3" CMOS sensor, 4 MP
- Up to 4MP (2560x1440) at 20 fps
- 2.8 ~ 12mm motor lens with autofocus
- H.265 +, H.265, H.264 +, H.264 video compression
- Dual stream
- WDR 120dB, BLC, 3DDNR, 1 ROI
- IR of 30 meters
- MicroSD card slot up to 128GB (card not included)
- IP67
- IK10
- PoE supported

SPECS

- 1/3" CMOS, 4 MP
- Digital resolution: 4MP (2560x1440), 3MP (2304x1296), 1080P (1920x1080), 1.3MP (1280x960), 720P (1280x720), etc.
- Compression format H.265 + / H.265 / H.264 + / H.264 / MJPEG
- Main Stream: 4MP (20 ips), 3MP, 1080P, 1.3MP, 720P (25 fps)
- Secondary stream: 640x480, 640x360, 320x240 (25 fps)
- Day / night mode with removable mechanical filter
- Infrared lighting: 30 meters
- 0.02 lux F1.6 color / 0 lux IR On
- 2.8 ~ 12mm motorized lens with autofocus
- Viewing angle: 92.8 ° ~ 29 ° (H), 50.2 ° ~ 16.4 ° (V), 109 ° ~ 32.3 ° (D)
- OSD menu
- White balance adjustable from client software or web browser
- Automatic gain control
- Backlight Compensation: BLC
- WDR 120dB
- 3D digital noise reduction
- 1 fixed ROI zone main and secondary stream
- Video sensor and privacy mask
- Adjust brightness, saturation, contrast and sharpness using client software or web browser
- MicroSD card slot up to 128GB (card not included)
- Reset button
- Network interface: RJ45 (10 / 100M) autoadaptive
- Network protocols: TCP / IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, NTP, UPnP, SMTP, IGMP, 802.1X, QoS, IPv6, UDP, Bonjour
- Compatible with ONVIF (Profile S, G), ISAPI
- Plug & Play connection with NVR NEXTGEN
- DDNS DEMES compatible
- Compatible with IE8 +, Chrome 3144, Firefox30-51, Safari 8+ browsers
- Power supply: 12V DC (± 25%)

- Consumption: 11W (PoE 12.5W)
- Supports 802.3af PoE, class 3
- Operating temperature of 30 ° C ~ + 60 ° C
- Humidity: 95% (no condensation)
- IP67
- IK10
- Metal case
- Dimensions: Ø138 x 110 mm
- Weight: 560 g
- 3AXIS: 0 ° ~ 360 ° (PAN), 0 ° ~ 75 ° (TILT), 0 ° ~ 360 ° (ROTATION)
- Power supply is not included