

IP BULLET CAMERA NIGHT FIGHTER WITH SMART IR 50M, FOR OUTDOORS 2 MP

KEY FEATURES

- IP bullet camera Night Fighter with Smart IR 50m, for outdoors 2 MP
- Triple Stream
- H.264/MPEG4/MJPEG
- 1/1,8" CMOS, 2MP
- Digital resolution 1080P, 1,3MP, 720P
- Mechanical filter
- 0,0027 lux
- 8~32 mm motor lens with autofocus
- OSD, AGC, BLC, real WDR 120dB, 3D-DNR, ROI, motion detection, ROI, defog
- LPR function, integrated LPR
- IVS
- Facial detection
- 2 way audio
- Alarm: 1 in / 1 out
- MicroSD slot
- IP67
- 3AXIS bracket
- Reset button
- 12V DC
- PoE
- Bracket and tube base included



NightFighter 



FEATURES

- 1/1,8" CMOS sensor, 2 MP
- Digital resolution: 1080P (1920x1080), 1,3MP (1280x960), 720P (1280x720), D1 (704x576), VGA (640x480), CIF (352x288)
- H.264/MPEG4/MJPEG
- Stream 1: 1080P, 1,3MP, 720P (50/60 fps)
- Stream 2: D1, VGA, CIF (25/30 fps)
- Stream 3: 1080P, 1,3MP, 720P, D1, VGA, CIF (25/30 fps)
- Day/night mode with removable mechanical filter
- Smart IR: 50 meters
- IR anti-reflective panel that increases the transmission of infrared light
- Minimum illumination: 0,0027 lux F1.4 (AGC On) / 0 lux IR On
- 8 ~ 32 mm motorized lens with autofocus
- OSD menu
- White balance
- AGC
- BLC
- Real WDR 120dB
- 3D digital noise reduction
- 1 fixed ROI
- Adjustment: rotation, brightness, saturation, contrast and sharpness via client software and web browser.
- Motion detection, regional cut, distortion correction, EIS, defog
- Image rotation, adjustment of brightness, saturation, contrast, sharpness, mirror
- Overlaying logos in BMP format with an area of 128x128
 - **Embedded LPR:** Configuration recognition area and country, 96% recognition accuracy (up to 70 km/h supported speeds)
- IVS: tripwire, intrusion, removed objects, input/output areas, scene change detection, detection of sudden increase / decrease of audio, detection of loss of audio, detection of blur, facial detection, object counting, etc.
- 6 behavior analysis, 4 exception detection, 1 recognition, 1 statistics functions
- Intelligent recorder: recording limit supported and dual VCA
- MicroSD/SDHC/SDXC card slot (up to 128 GB)
- BNC video output
- Audio: 1 in / 1 out
- Alarm: 1 in / 1 out
- Reset button
- Network interface: RJ45 (10/100M)
- Network protocols: TCP/IP, UDP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Bonjour
- Compatible with ONVIF (Profile S, G), PSIA, CGI, ISAPI
- Plug&Play connection with NEXTGEN NVR
- Compatible with DDNS DEMES
- Power supply: 12V DC ($\pm 10\%$) /12W
- PoE 802.3af supported
- Working temperature -30°C ~ +60°C
- RH: 95%
- IP67
- Dimensions: 100 x 103,9 x 311,8 mm
- Weight: 2 kg
- 3AXIS bracket
- Power supply is not included
- Wall mount and tube base included