

4 IN 1 HYUNDAI NEXT GEN DOME ULTRAPRO SERIES WITH SMART LIGHT OF 20 M FOR OUTDOORS



KEY FEATURES

- 4 in 1 HYUNDAI NEXT GEN dome ULTRAPRO series with Smart Light of 20 m for outdoors
- 2MP CMOS
- 1080P resolution @ 25 / 30ips Switchable 4-in-1 video output
- 2.8 mm lens
- ICR filter AWB, AGC, BLC, HLC, HLS, WDR 130dB, 2D / 3D-DNR, Anti flicker, motion detection and privacy masks
- It incorporates PIR detector, strobe and siren
- 1 alarm output IP67 3AXIS
- 12V DC

FEATURES

- StarLight technology
- 2 MP CMOS
- 1080P (1920x1080) at 25 fps
- 2,8 mm lens
- PIR detection incorporation
- Strobe light alarm and audible alarm with builtin siren
- WDR 130dB, 2D/3DDNR
- Smart Light up to 20 meters
- 1 alarm output
- 4 in 1 video output switch
- IP67

SPECS

- 2 MP CMOS
- Digital resolution: 1080P (1920x1080)
- Frames per second:
 - TVI: 1080P (25/30 fps)
 - AHD: 1080P (25/30 fps)
 - CVI: 1080P (25/30 fps)
 - CVBS: PAL/NTSC
- 4 in 1 video output switch (HDCVI, HDTV, AHD, CVBS)
- No switch to black and white, 24h color mode
- 0,0005 lux F1.0 (color) / 0 lux white leds ON
- Smart Light (white light): 20 meters
- 2,8 mm lens
- Auto/manual white balance
- Automatic gain control
- Backlight compensation: BLC, HLC, HLS
- WDR 130dB
- 2D/3D DNR
- Brightness adjustment, Sharpness, mirror, Smart Light and defective pixel correction
- Standard and high saturation image modes
- Anti blink (antibanding)
- 4 programmable video sensor
- 4 programmable privacy masks
- 1 alarm output
- PIR detection with a coverage of 11 meters, 110 °
- Flashing light alarm (red and blue)
- Sound alarm
- Power supply: 12V DC (± 25%)
- Consumption: Max. 6.6W
- Operating temperature of 40 ° C ~ + 60 ° C
- Relative humidity: <90% (no condensation)
- Degree of protection IP67
- Metal and plastic case
- Dimensions: Ø109.8 x 93.7 mm
- Weight: 390 g