

GF-GF double F type socket (professional)



Edition: 1 from 01.06.2017
Supercedes the edition: -----

EN



1. Technical description.

The GF-GF double F type socket (professional) is used to make connections between two different types of coaxial cables, e.g. RG6, RG59, and RG11, terminated with an "F" type plug. The impedance of the connector is 75 Ohm.

This element, commonly referred to as "barrel", is used in antenna installations (terrestrial, satellite, CATV, etc.). The socket is made of nickel plated brass, which increases its corrosion resistance.

2. Technical parameters.

Code	GF-GF
Connector type	F socket – F socket
Attenuation	0,05dB
Dimensions: (diameter/length)	∅ 7mm / 27 mm
Net / gross weight	0,07kg
Declarations, warranty	CE, 1 year from the production date

WEEE LABEL

Waste electrical and electronic equipment must not be disposed of with normal household waste. According to the European Union WEEE Directive, waste electrical and electronic equipment should be disposed of separately from normal household waste.

Pulsar

Siedlec 150, 32-744 Łapczyca, Poland
Tel. (+48) 14-610-19-40, Fax. (+48) 14-610-19-50
e-mail: biuro@pulsar.pl, sales@pulsar.pl
http:// www.pulsar.pl, www.zasilacze.pl