

HD-TVI DOME PRO SERIES WITH SMART IR OF 40 M FOR OUTDOORS



KEY FEATURES

- HD-TVI dome PRO series with Smart IR of 40 m for outdoors
- 5MP CMOS
- HD-TVI video output
- 2,7~13,5 mm motorized lens (95,7°~29,1°)
- ICR
- OSD, ATW, MWB, AGC, BLC, digital WDR, 2D-DNR, image adjustment
- IP67
- 3AXIS
- 12V DC
- PoC.at compatible

FEATURES

- 5MP CMOS sensor
- Digital resolution: 5MP (2560x1944) at 20 fps, 4MP/1080Pat 25 fps
- HDTV video output
- 0,01 lux F1.2 (color, AGC On) / 0 lux IR On
- Removable mechanical filter
- Smart IR: EXIR 2.0 technology, 40meters
- 2,7 ~ 13,5 mm motorized lens (95,7°~29,1°)
- OSD via coaxial (300 m range)
- ATW/MWB
- Automatic gain control
- BLC
- Digital WDR
- 2D-DNR
- Mirror mode supported
- Adjustment: brightness and sharpness
- Working temperature -40°C~+60°C
- RH 90% (without condensation)
- IP67
- Metal case
- Power supply: 12V DC (±25%)
- Consumption: 7,8W
- PoC.at supported specially for ZVR PoC
- Dimensions: 123,9x134,3 x 110,1 mm
- Weight: 620 g
- 3AXIS: wall and ceiling installation

RELATED PRODUCTS

