



KEY FEATURES

- 16 channel 5 in 1 ZVR HDCVI/HDTVI/AHD/CVBS + 8 IP channels
- H.265+/H265/H.264+/H264
- Audio: 4 in / 1 out
- 16 channels simultaneous playback
- Recording: 8MP (TVI), 6MP (IP), 5MP (TVI, AHD), 4MP, 1080P, 720P, WD1, 4CIF, VGA, CIF
- Salida BNC a 4CIF
- HDMI (4K, 2K) and VGA (1080P)
- Alarm: 4 in / 1 out
- 2 HDD SATA
- RJ45 Gigabit

16 CHANNEL 5 IN 1 ZVR HDCVI/HDTVI/AHD/CVBS + 8 IP CHANNELS

- 16 channel 5 in 1 ZVR H.265+/H265/H.264+/H.264
- 5 technologies: IP, HDCVI, HDTVI, AHD and CVBS
- PoCup to 5MP for HD-TV compatible cameras (up to 200 m)
- H.265+
- 16 BNC input (coaxitron supported):
- HDCVI: 4MP, 1080P, 720P (telemetry control by coaxial cable of HDCVI cameras)
- HDTVI: 8MP, 5MP, 4MP, 3MP, 1080P, 720P
- AHD: 5MP, 4MP, 1080P/720P
- CVBS: 960H
- 8 IP inputs up to 6MP (added to BNC inputs)
- Possibility of assigning several or all analog channels to IP channels
- VGA (1080P) and HDMI (4K, 2K) output
- BNC auxiliary output up to 704x576
- 4 RCA in / 1 RCA out
- 2 way audio
- Display resolution: 8MP, 6MP, 5MP, 4MP, 3MP, 1080P, 720P, WD1, 4CIF, VGA, CIF
- Recording resolution: 8MP (TVI), 6MP (IP), 5MP (TVI, AHD), 4MP, 3MP, 1080P, 720P, WD1, 4CIF, VGA, CIF
- Stream 1: 8MP (8 fps), 5MP (12 fps), 4MP (15 fps), 3MP (18 fps), 1080P/720P/WD1/4CIF/VGA/CIF (25 fps)
- Stream 2: WD1/4CIF/CIF (25 fps)
- Simultaneous playback: 16 channels
- Alarm: 4 in / 1 out
- 2 HDD SATA up to 10TB (not included)
- HDD quota mode supported; different capacities to different channels
- GUI and start recording key (Wizard)
- Video quality diagnosis
- Playback and search by tag
- Lock/unlock log file
- Ethernet network interface: RJ45 (10/100/1000M) auto-adaptive
- Network protocols: TCP/IP, PPPoE, DHCP, P2P, DNS, DDNS, NTP, SADP, NFS, iSCSI, UPnP™, HTTPS
- Compatible with ONVIF
- Remote access up to 128 users
- Remote access via iPhone/iPad, Android
- Multi browser compatibility: Chrome, Firefox, Safari, IE
- P2P cloud, DDNS DEMES, Push and channel zero
- Connections: 1 USB 2.0, 1 USB 3.0, 1 RS485 half-duplex
- Power supply: 100V ~ 240V AC
- Consumption: ≤140W
- Working temperature: -10°C ~ +55°C
- RH: 10~90%
- Dimensions: 380 x 320 x 48 mm (desktop)
- Weight: ≤3,8 kg (without HDD)