



**HDCVI HDTVI AHD CVBS**

### KEY FEATURES

- 4 in 1 PTZ dome, 120°/sec
- con IR illumination of 120 m, for outdoors
- 1/3" Sony CMOS, 2MP at 1080P
- 4 in 1 output (HDCVI / HDTVI / AHD / 960H)
- 20X optical zoom of 5,35~107 mm (68,5°~4,2°)
- ICR filter
- 0,1/0,01 lux
- OSD, AWB, AGC, BLC, digital WDR
- 220 presets
- RS485

## SAM-4050 SAM-4050

4 IN 1 PTZ DOME, 120°/SEC . CON IR ILLUMINATION OF 120 M, FOR OUTDOORS

- 1/3" Sony® CMOS sensor
- Digital resolution: 1080P (1920x1080)
- Live transmission without video loss
- Removable mechanical filter
- IR illumination: Leds array, 120meters
- Minimum illumination: 0,1 lux (color) / 0,01 lux (B/W)
- 20X optical zoom: 5,35~107 mm
- Viewing angle: 68,5°~4,2°(H)
- 4 in 1 output: HDCVI / HDTVI / AHD / CVBS 960H
- On screen menu via coaxial (500 meter range, only on CVI/TVI/AHD modes)
- White balance: indoor, outdoor, auto, manual
- Automatic Gain Control
- Backlight compensation(BLC)
- Digital WDR
- Horizontal positioner: 360°, autoflip 180°
- Vertical positioner: 93°, autoflip 93°
- Speed: 0,02°~120°/sec. (H), 0,02°~60°/sec. (V)
- Preset speed:1~64degrees
- 220 presets
- Communication:RS485, coaxial cable
- 3 round groups, 16 guard points, A-B Scan (1~64 degrees)
- Baud rate: 9600bpsdefault
- Power supply: 12V DC /3A
- Consumption:≤15W
- Working temperature (indoor): 0°C ~ +40°C
- Working temperature (outdoor): -40°C ~ +60°C
- RH:≤95% (without condensation)
- Heater/fan with automatic temperature control
- IP66
- 6KV Lightning-proof
- Metal case
- 7" dome
- Wall mount and power supply included