

IP VANDAL DOME PERFORMANCE LINE WITH IR OF 30M, FOR OUTDOORS 6 MP



PerformanceLine **6MP** **H.265**

PRP ONVIF

KEY FEATURES

- IP vandal dome Performance Line with IR of 30m, for outdoors 6 MP
- H.265+/H.265/H.264/H.264+/MJPEG
- 1/2,9" CMOS, 6MP
- Digital resolution: 6MP, 5MP, 4MP, 1080P, 720P, 20FPS
- Mechanical filter

FEATURES

- 1/2,9" CMOS sensor, 6 MP
- Digital resolution: 6MP (3072x2048), 5MP (3072x1728), 5MP (2944x1656), 4MP (2560x1440), 1080P (1920x1080), 720P (1280x720), etc.
- H.265+/H.265/H.264+/H.264/MJPEG
- Stream 1: 6MP/5MP (20 fps), 4MP/1080P/720P (25 fps)
- Stream 2: VGA/QVGA (25 fps)
- Stream 3: 720P/VGA/CIF (25 fps)
- Day/night mode with removable mechanical filter
- IR illumination: 30meters
- Minimum illumination: 0,01 lux F1.2 color / 0,028 lux F2.0 color / 0 lux IR On
- 2,8 mm (97°) fixed lens
- OSD menu, AGC, BLC, real WDR 120dB, 3D-DNR
- 1x fixed ROI stream 1 and stream2
- Motion detection and privacy mask
- Adjustment: brightness, saturation, contrast, sharpness, mirror mode, image rotation
- IVS: Tripwire, intrusion detection
- Facial detection
- MicroSD/SDHC/SDXC card slot up to 128GB (card is not included)
- Network interface: RJ45 (10/100 Base-T)
- Network protocols: TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Bonjour
- Compatible with ONVIF (profile S/G), PSIA, CGI, ISAPI
- Plug&Play with NVR NEXTGEN
- Compatible with DDNS DEMES
- Power supply: 12V DC, max 7,5W
- PoE 802.3af supported (36V ~ 57V CC; 0,3A ~ 0,2A; max. 9W)
- Working temperature: -30°C ~ +60°C
- RH: <95%, without condensation
- IP67
- IK10
- Metal and plastic case
- Dimensions: Ø111 x 82,4 mm
- Weight: 500 g
- 3AXIS: wall and ceiling installation
- Power supply is not included
- Reset button

RELATED PRODUCTS

