



PerformanceLine **IP67** **P2P**



KEY FEATURES

- IP vandal dome with IR of 30m, for outdoors, 4 MP
- H.265+/H.265/H.264/H.264+/MJPEG
- 1/3" CMOS, 4MP
- Digital resolution 4MP, 1080P, 720P, 20FPS
- Mechanical filter
- 0,01 lux
- 2,8~12 mm (98°~30°) motor lens with autofocus
- OSD, AGC, BLC, real WDR 120dB, 3D-DNR, motion detection, privacy mask, fixed ROI
- MicroSD/SDHC/SDXC
- IP67, IK10

IP VANDAL DOME WITH IR OF 30M, FOR OUTDOORS, 4 MP

- 1/3" CMOS, sensor 4 MP- Digital resolution: 4MP (2560x1440), 1080P (1920x1080), 720P (1280x720), etc.- H.265+/H.265/H.264+/H.264/MJPEG- Stream 1: 4MP, 1080P, 720P (20 fps)- Stream 2: D1, CIF, VGA, QVGA (20 fps)- Day/night mode with removable mechanical filter- IR illumination: 30 metros- Minimum illumination: 0,01 lux F1.2 color / 0,018 lux F1.6 color / 0 lux IR On- 2,8 ~ 12 mm (98°~28°) motor lens with autofocus- OSD menu, AGC, BLC, real WDR 120dB, 3D-DNR- 1 fixed ROI stream 1 and stream 2- Motion detection and privacy mask- Adjustment: brightness, saturation, contrast, sharpness, mirror- MicroSD/SDHC/SDXC card slot (up to 128 GB)- Network interface: RJ45 (10/100 Base-T) - Network protocols: TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802,1X, QoS, IPv6 UDP, Bonjour- Compatible with ONVIF (Profile S, G), ISAPI- Plug&Play with NVR NEXTGEN- Compatible with DDNS DEMES- Power supply: 12V DC /10W (PoE 12W)- PoE 802.3af supported, class 3- Working temperature: -30°C ~ +60°C- RH: 95% (without condensation)- IP67- IK10- Lightning-proof 2KV- Metal case- Dimensions: Ø141 x 99,9 mm- Weight: 800 g- 3AXIS: wall and ceiling installation- Power supply is not included