

IP DOME, 5MP WITH IR OF 30M, VANDAL PROTECTION FOR OUTDOORS



KEY FEATURES

- IP dome, 5MP with IR of 30m, vandal protection for outdoors
- H.265+/H.265/H.264+/H.264/MJPEG
- 1/2,7" CMOS, 5MP
- 5MP@12,5FPS
- ICR filter
- 0,02 lux
- 2,8 ~12 mm motor lens (98°~28°)
- OSD, AGC, BLC, real WDR 120dB, 3D-DNR, motion detection, privacy mask, 1 fixed ROI
- Reset button
- MicroSD

FEATURES

- 1/2,7" CMOS sensor, 5 MP
- Digital resolution: 5MP (2560x1920), 4MP (2560x1440), 3MP (2304x1296), 1080P (1920x1080), 720P (1280x720), etc.
- H.265+/H.265/H.264+/H.264/MJPEG
- Stream 1: 5MP (12,5 fps), 4MP (20 fps), 3MP/1080P/720P (25 fps)
- Stream 2: 640x480, 640x360, 320x240 (25 fps)
- Day/night mode with removable mechanical filter
- IR illumination: 30 meters
- Minimum illumination: 0,02 lux F1.6 color / 0 lux IR On
- 2,8 ~12 mm motor lens with autofocus
- Viewing angle: 98°~28°(H), 71°~21°(V)
- OSD menu
- AGC, BLC
- Real WDR 120dB
- 3D Digital Noise Reduction
- 1 fixed ROI stream 1 and stream 2
- Motion detection and privacy mask
- Adjustment: brightness, saturation, contrast and sharpness via client software and web browser
- Reset button
- MicroSD/SDHC/SDXC up to 128GB (card is not included)
- Network interface: RJ45 (10/100 Base-T)
- Network protocols: TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, QoS, IPv6, UDP, Bonjour, 802.1x
- Compatible with ONVIF (Profile S, G), ISAPI
- Plug&Play with NVR NEXTGEN
- Compatible with DDNS DEMES
- Power supply: 12V DC
- Consumption: 0,8A, max. 10W
- PoE 802.3af supported
- Working temperature -30°C ~ +60°C
- RH: 95% (without condensation)
- IP67
- IK10
- PVC and metal case
- Dimensions: Ø141 x 99 mm
- Weight: 800 g
- 3AXIS: 0°~355°(PAN), 0°~70°(TILT), 0°~355°(Rotation)
- Power supply is not included